

Technical Data Sheet

2018-P

Heavy Duty Paint Marker

SPEEDY®

FEATURES:

- Valve-Action markers allow more control over ink flow and keep the ink in the barrel from drying out if the cap is left off.
- Replaceable tips extend the life of your markers.
- Opaque paint markers will clearly mark on dark or light surfaces.
- Great for metal, wood, corrugated, rubber, plastic, glass and other hard to mark surfaces.
- Available in 9 weather & fade resistant colors.
- Sold by color in boxes of 12. Cartons include 12 boxes / 144 markers.

COMPATIBILITY:

- Safe for most porous & non-porous surfaces.
- Test on surfaces prior to use to ensure compatibility.

DIRECTIONS FOR USE:

- Shake marker until you hear the agitator
- Twist the cap off
- Gently pump until the tip is primed

HEALTH & SAFETY:

- Use only with proper ventilation.
- Flammable liquid & vapor: keep away from ignition sources like flames, sparks, or electrostatic charges.
- Avoid skin and eye contact and ingestion.
- For complete health & safety data, refer to MSDS at www.diagraphmsp.com

TECH SPECS:

- Standard Stroke Width: 1/8"
- Fill Quantity: ~1/2 oz
- Barrel Size: .625" Diameter x 4.125" Long

PHYSICAL PROPERTIES:

Color	Part No.	Specific Gravity	VOC Level	Flash Point	Resistant to	Dry Time
Black	0950001	0.990	5.6 lbs/gal	70°F (21.1°C)	600°F	20-30 Sec
Blue	0950002	1.147	5.3 lbs/gal	75°F (23.9°C)	500°F	20-30 Sec
Light Green	0950004	1.267	5.9 lbs/gal	75°F (23.9°C)	600°F	20-30 Sec
Orange	0950005	1.088	5.2 lbs/gal	75°F (23.9°C)	500°F	20-30 Sec
Red	0950007	1.043	5.6 lbs/gal	75°F (23.9°C)	500°F	20-30 Sec
White	0950009	1.284	5.6 lbs/gal	77°F (25.0°C)	500°F	20-30 Sec
Yellow	0950010	1.189	5.1 lbs/gal	77°F (25.0°C)	500°F	20-30 Sec
Green	0950013	1.175	5.5 lbs/gal	75°F (23.9°C)	600°F	20-30 Sec
Pink	0950016	1.282	5.5 lbs/gal	75°F (23.9°C)	500°F	20-30 Sec