



**classic**  
VALVE ACTION | all purpose paint marker



## Technical Data Sheet

### FEATURES:

- Valve-Action markers allow more control over ink flow and keep the ink in the barrel from drying out if the cap is left off.
- Replaceable tips extend the life of your markers.
- Opaque paint markers will clearly mark on dark or light surfaces.
- Great for metal, wood, corrugated, rubber, plastic, glass and other hard to mark surfaces.
- Available in 8 weather & fade resistant colors.
- Sold by color in boxes of 12. Cartons include 12 boxes / 144 markers.
- Assortment packs (0968525) include 1 of each color (8 markers total).

### COMPATIBILITY:

- Safe for most porous & non-porous surfaces.
- Test on surfaces prior to use to ensure compatibility.

### DIRECTIONS FOR USE:

- Shake marker until you hear the agitator
- Twist the cap off
- Gently pump until the tip is primed

### HEALTH & SAFETY:

- Use only with proper ventilation.
- Flammable liquid & vapor: keep away from ignition sources like flames, sparks, or electrostatic charges.
- Avoid skin and eye contact and ingestion.
- For complete health & safety data, refer to MSDS at [www.diagraphmsp.com](http://www.diagraphmsp.com)

### TECH SPECS:

- Standard Stroke Width: 1/8"
- Fill Quantity: ~1/2 oz (~13 cc)
- Barrel Size: .563" Diameter x 4.75" Long

### PHYSICAL PROPERTIES:

| Color  | Part No. | Specific Gravity | VOC Level   | Flash Point   | Resistant to | Dry Time  |
|--------|----------|------------------|-------------|---------------|--------------|-----------|
| Black  | 0918500  | 0.990            | 5.6 lbs/gal | 70°F (21.1°C) | 600°F        | 20-30 Sec |
| Yellow | 0958500  | 1.189            | 5.1 lbs/gal | 77°F (25.0°C) | 500°F        | 20-30 Sec |
| White  | 0968500  | 1.284            | 5.6 lbs/gal | 77°F (25.0°C) | 500°F        | 20-30 Sec |
| Blue   | 0968521  | 1.147            | 5.3 lbs/gal | 75°F (23.9°C) | 500°F        | 20-30 Sec |
| Red    | 0968520  | 1.043            | 5.6 lbs/gal | 75°F (23.9°C) | 500°F        | 20-30 Sec |
| Green  | 0968522  | 1.175            | 5.5 lbs/gal | 75°F (23.9°C) | 600°F        | 20-30 Sec |
| Orange | 0968523  | 1.088            | 5.2 lbs/gal | 75°F (23.9°C) | 500°F        | 20-30 Sec |
| Silver | 0968524  | 0.921            | 6.4 lbs/gal | 75°F (23.9°C) | 800°F        | 20-30 Sec |