

SHINY GALV

#16-841



A shiny zinc enhanced zinc coating that prevents rust and provides excellent outdoor protection. This is the product of choice for the cosmetic restoration of galvanized metal, chain link fences, and guard rails. *Does not* meet specifications calling for 65% zinc in the can or greater than 90% zinc in the dried paint film. Fast dry, prevents rust, and has excellent outdoor durability.

Suggested Uses:

All vehicle bodies
Agricultural, mining and construction equipment
Piping, storage tanks
Bridges
Ships and marine equipment

Packaging:

UPC Code	043281007221
Cans per case	6
Shipping weight per case	7 lbs.
Container	16 fluid ounce can
Label weight	12 ounces (340 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Flammability	"Extremely Flammable"
Flash point	-4 ^o F
Specific Gravity	0.78
Solids Content	~23%
VOC content	~59%, cannot exceed 80%
Zinc in dried paint film	~4%
MIR value	~1.85, cannot exceed 1.90
HAPs content	~32%
Storage Temperature	40-100F
Application Temperature	50-90F
Durability	Very Good
Abrasion Resistance	Good
Heat Resistance	250 ^o F
Resin System	Chain Stopped Alkyd
Shelf life	Guaranteed for 2 years
Food contact rating	No

Dry Time*:

To touch	10 minutes
To topcoat	before 1 hour or After 48 hours

*At 72^oF, 50% humidity,
1.5 mil thickness

**Curing/Recoat time is extended with
multiple coats and excessively thick
coats**

Gloss*: Flat, <15*

*as measured on a 60^o gloss meter